



SPF 30 Daily Wear Sunscreen

BOT.19.04.C

This anti-aging SPF 30 formulation designed for daily use demonstrates the benefits of incorporating Capsol™ to allow for lower use levels of sunscreen while achieving the same SPF level, enhancing aesthetics, and improving wear resistance and skin moisturization.

PHASE	%	INGREDIENT	INCI	FUNCTION
1	65.00	Deionized Water	Water	Aqueous Vehicle
1	0.25	Keltrol® CG-SFT	Xanthan Gum	Rheology Modifier
1	3.00	Glycerin	Glycerin	Humectant
2	4.00	Octocrylene	Octocrylene	UV Filter
2	1.00	Octyl Salicylate	Octisalate	UV Filter
2	2.00	Homosalate	Homosalate	UV Filter
3	2.00	Avobenzene	Butyl Methoxydibenzoylmethane	UV Filter
3	5.00	Finsolv® PG-22	Dipropylene Glycol Dibenzoate	Solubilizer
3	2.50	Cetiol® CC	Dicaprylyl Carbonate	Emollient
3	1.50	Lexfilm® Sun	Polyester-7 (and) Neopentyl Glycol Diheptanoate	Solubilizer
4	10.00	CapSol™	Carthamus Tinctorius (Safflower) Oleosomes (and) Water	Multi-functional Emulsifier
5	0.75	Aristoflex® AVC	Ammonium Acryloyldimethyltaurate/VP Copolymer	Thickener
6	1.50	White Birch BT	Water (and) Betula Alba Bark Extract (and) Phenoxyethanol (and) Sodium Benzoate	Active
6	1.50	Resveratrol BT	Water (and) Polygonum Cuspidatum Root Extract (and) Phenoxyethanol (and) Sodium Benzoate	Antioxidant
7	qs	Sodium Hydroxide Sol. 18%	Sodium Hydroxide	Neutralizing Agent
8	qs	Preservative	Preservative	Preservative
	100.00%			

PROCEDURE:

1. Premix Keltrol® CG-SFT and Glycerin into a slurry, then add to Deionized Water in main vessel with medium speed propeller stirring.
2. Add Phases 2 ingredients in side vessel and thoroughly mix with propeller stirring until homogeneous.
3. Premix Phase 3 ingredients while heating at 45°C until homogeneous, and then add to Phase 2 side vessel with continued thorough mixing.
4. Add Phase 4 to Phases 2-3 side vessel with continued thorough mixing at 300-400 rpm for 20 minutes, or until uniform.
5. Add combined Phases 2-4 ingredients to main vessel and continue thoroughly mixing at increased speed of 600-800 rpm for 20 minutes, or until uniform.
6. Slowly Add Phase 5 ingredient to main vessel with continued thorough mixing until homogeneous.
7. Switch to sweep blade and lower mixing speed. Add Phase 6 ingredients, one by one, and continue thoroughly mixing.
8. Use Phase 7 ingredient to adjust pH to 5.5 - 6.0.
9. Add Phase 8 ingredient and finish thoroughly mixing. Pour into suitable container(s).

Product: CapSol™

pH: 5.5-6.0

Formula Ref. #: 048-19B



Information contained in this literature is believed to be accurate and is offered in good faith for the benefit of the customer. This company, however, cannot assume any liability or risk involved with the use of its products since the conditions of use are beyond our control. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patents. The customer must insure that its uses of our products are non-infringing. We make no warranty of any kind, expressed or implies other than the material conforms to the standard applicable specifications.

Sales and Technical Support 403.668.6685

sales@botaneco.com